

# Material Safety Data Sheet

## **SANTOLUBES LLC**

SANTOTRAC, SANTOVAC, SANTOLUBES AND SYNERGY  
P.O. Box 960  
St. Charles MO 63302-0960

Page 1 of 4

---

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

PRODUCT NAME: **SANTOTRAC® 32 TRACTION LUBRICANT**

Chemical Family: Synthetic Hydrocarbon

CHEMICAL EMERGENCY: Call CHEMTREC 1-800-424-9300 or 703-527-3887

For additional non-emergency information, call: 636-723-0240

---

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

---

Synthetic Hydrocarbon: 70 –99%

Balance is Proprietary Additive Package

---

### 3. HAZARDS IDENTIFICATION

---

Primary routes of exposure:

Eye contact: Material can cause slight to moderate irritation.

Skin contact: Slight to moderate irritation is expected.

---

### 4. FIRST AID MEASURES

---

EYES: Immediately flush with plenty of water for at least 15 minutes. Call a physician.

SKIN: Wipe off excess and wash with soap and plenty of water. Remove contaminated clothing. Wash clothing before reuse.

---

### 5. FIRE FIGHTING MEASURES

---

Flash Point (COC): 325°F (163°C)

Auto Ignition Temperature: 620°F (327°C)

Extinguishing Media: Water spray, foam, dry chemical, carbon dioxide or any Class B extinguishing agent.

Special Fire Fighting Procedures: Fire fighters or others likely to be exposed to products of combustion should wear full protective clothing including self-contained breathing apparatus. Equipment should be thoroughly decontaminated after use.

Unusual Fire and Explosion Hazards: Products of decomposition include carbon monoxide, carbon dioxide, and hydrocarbons.

---

### 6. ACCIDENTAL RELEASE MEASURES

---

IN CASE OF SPILL OR LEAK: Absorb with a suitable media such as sawdust, clay or filtercel.

---

## 7. HANDLING AND STORAGE

---

SANTOTRAC® 32 lubricant is stable under ordinary handling and storage conditions.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

Eye Protection: SANTOTRAC® 32 Traction Lubricant causes only slight eye irritation. No special protection required. Avoid eye contact as good industrial practice.

Skin Protection: Wear appropriate protective gloves that provide a barrier and protective clothing to prevent skin contact. Consult glove manufacturer to determine appropriate type glove for given application. Wear face shield and apron when splashing is likely. Wash contaminated skin promptly. Launder contaminated clothing and clean protective equipment before reuse. Wash thoroughly after handling.

Respiratory Protection: Avoid breathing vapor or mist. Use NIOSH/MSHA approved equipment. The respirator use limitations specified by NIOSH/MSHA or the manufacturer must be observed. High airborne concentrations may require use of self-contained breathing apparatus or supplied air respirator. Respiratory protection programs must be in compliance with 29 CFR 1910.134.

Ventilation: Provide ventilation to minimize exposure. Use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Appearance:	Slightly turbid yellow liquid
Density @ 25°C:	0.88 – 0.92 g/cc
Viscosity @ 100°F:	29-35 centistokes
Solubility in Water:	Very low

---

## 10. STABILITY AND REACTIVITY

---

Stability: SANTOTRAC® 32 lubricant is stable under ordinary handling and storage conditions.

Materials to Avoid: Exposure to highly oxidizing materials should be avoided.

Hazardous Decomposition Products: No uniquely hazardous decomposition products are expected. If the product is burned, carbon dioxide, carbon monoxide, low molecular weight hydrocarbons, soot, and smoke can be produced.

Hazardous Polymerization: Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

### Toxicological Data

Findett has not conducted acute toxicity studies with SANTOTRAC® 32. However, the following acute data were developed on the synthetic hydrocarbon base fluid, and are considered to be representative of SANTOTRAC® 32.

Oral LD50 (Rat): Greater than 15,800 mg/kg, Practically Nontoxic

Dermal LD50 (Rabbit): Greater than 7,940 mg/kg, Practically Nontoxic

Eye Irritation (Rabbit, 24-hr): 3.5 on a scale of 110.0, Slightly Irritating

Skin Irritation (Rabbit, 24-hr): 0.0 on a scale of 8.0, Nonirritating

Vapor Inhalation (Rat): Rats were exposed to a stream of air passed through the lubricant and led directly into the experimental chamber. Due to its low volatility, there was essentially no vaporization of the test material and the animals survived both the 6-hour exposure and subsequent 10-day observation periods without observable effects.

---

## **12. ECOLOGICAL INFORMATION**

---

SANTOTRAC® 32 had a primary degradation rate of 7% to 21% in a 24-hour semi-continuous activated sludge test (SCAS). Biodegradability of this material was classified as slow to resistant.

Oral LD50 Mallard Duck: Greater than 4,640 mg/kg, Practically Nontoxic

Oral LD50 Bobwhite Quail: Greater than 4,640 mg/kg, Practically Nontoxic

96-hr LC50 Fathead Minnow: Greater than 1,000 mg/l, Practically Nontoxic

The bioaccumulation potential in bluegill sunfish was measured over a 32-day period. It was determined that this material has a moderate potential to bioaccumulate in this aquatic specie.

---

## **13. DISPOSAL CONSIDERATIONS**

---

This material when discarded is not a hazardous waste as defined by the Resource, Conservation and Recovery Act (RCRA), 40 CFR 261. Dispose of in accordance with all federal, state, and local environmental regulations. Recommended method of disposal is by high temperature incineration in a RCRA approved TSDF.

---

## **14. TRANSPORT INFORMATION**

---

Hazard Class:

This material is not classified as a hazardous material by the U.S. Department of Transportation (DOT) or by the International Air Transport Association (IATA).

---

## **15. REGULATORY INFORMATION**

---

SARA Hazard Notification Hazard Categories under Criteria of SARA Title III Rules (40 CFR Part 370): Immediate

Section 313 Toxic Chemical(s): Not Applicable

---

## **16. OTHER INFORMATION**

---

This is for people trained in the National Paint & Coatings Association's (NPCA) Hazardous Materials Identification System (HMIS) and the National Fire Protection Association (NFPA 704):


NPCA-HMIS

Name of Material	
<b>SANTOTRAC® 32</b>	
<b>0</b>	<b>HEALTH</b>
<b>1</b>	<b>FLAMMABILITY</b>
<b>0</b>	<b>REACTIVITY</b>
<b>B</b>	<b>PROTECTIVE EQUIPMENT</b>



NFPA 704

Flammability



HAZARD INDEX

0 = Minimal Hazard	1 = Slight Hazard	2 = Moderate Hazard	3 = Serious Hazard	4 = Severe Hazard
--------------------	-------------------	---------------------	--------------------	-------------------

SANTOTRAC® is a registered trademark of SANTOLUBES LLC

NOTICE: Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, SANTOLUBES LLC makes no representations as to the completeness or accuracy thereof. Information is supplied upon the conditions that the persons receiving same will make their own determinations as to its suitability for their purposes prior to use. In no event will SANTOLUBES LLC be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OR MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.